

SHOCK SPECS

P/N	POSITION	TOP HOLE	TOP EYELET	BOTTOM HOLE	BOTTOM	TUBE	STROKE	SPRING OD	SPRING WIRE	SPRING RATE	C TO C	
		I.D. MM	WIDTH MM	I.D. MM	EYELET WIDTH MM	O.D. MM		MM	DIAMETER MM			LBS/INCH
<b>STRUTS</b>												
AU-04300	FRONT	.5 X 36 THREADED ROD		N/A	N/A	38	136.6	80	8	62	1.10	486
AU-04310	FRONT	.5 X 36 THREADED ROD		N/A	N/A	41.5	147	96	10.5	-	-	493
AU-04315	FRONT	.5 X 36 THREADED ROD		N/A	N/A	41.4	173	91.5	8.7	-	-	561
AU-04331	FRONT	.5 X 36 THREADED ROD		N/A	N/A	41.3	168	86	9.3	-	-	553
AU-04347	FRONT	M10 BOLTS X3		N/A	N/A	44	-	93.5	9.2	179	3.20	426
AU-04400	FRONT	.5 X 38 THREADED ROD		N/A	N/A	42	136.6	97.5	9	69/99	1.23 / 1.76	480
<b>SHOCKS</b>												
AU-04202	FRONT	10	21	10	21	38	60	73	8.5	112	2.00	297
AU-04203	FRONT	10	20	10	24	38	68	73	9.5	202	3.60	345
AU-04205	FRONT	10	27.5	10	32	36	95	64	9	146	2.60	333
AU-04206	FRONT	10	28	10	32	38	55	72	9.5	-	-	302
AU-04207	FRONT	10	21	10	20	38	79.5	65	8.5	162	2.90	364
AU-04208	FRONT	10	21	10	24	38	100	72	9	162	2.90	389
AU-04209	FRONT	10	21	10	24	38	78.6	73	8.5	-	-	368
AU-04252	REAR	16	20	10	21	38	65	72	8.5	-	-	347
AU-04253	REAR	10	32	10	32	44	89.8	70	9.5	-	-	395
AU-04254	REAR	10	32	10	32	44	90.5	70	9.5	-	-	396
AU-04256	REAR	10	32	10	32	44	79	70	9.5	-	-	365
AU-04257	REAR	16	21	10	24	38	89.5	65	8	112	2.00	390
AU-04258	REAR	18	23	10	32	36	118	67	8	154	2.75	463
AU-04259	REAR	10	32	10	32	42	106	73	9	185	3.30	423
AU-04301	FRONT	10	30	10	35.5	50.8	127	81.5	9.5	112	2.00	408
AU-04302	FRONT	10	32	10	32	35.8	58	61.6	7 2/7	112	2.00	310
AU-04303	FRONT	10	32	10	32	39	98	74.5	7 1/2	-	-	362
AU-04304	FRONT	10	32	10	30	39	82	71	8	-	-	366
AU-04305	FRONT	10	32	10	30	39	87	70	8 1/3	-	-	358
AU-04306	FRONT	10	32	10	32	36	96	67	7 2/5	-	-	388
AU-04307	FRONT	10	32	10	30	38	64.8	73	9	-	-	360
AU-04308	FRONT	10	30	10	30	38	81.3	68	8.2	-	-	373
AU-04309	FRONT	10	32	10	32	39	93	74	9	-	-	402
AU-04309	FRONT	10	32	10	32	39	93	74	9	238	4.25	402
AU-04311	FRONT	10	20	10	30	36	48	66	9	-	-	255
AU-04312	FRONT	10	20	10	21	30	65.2	57	7.5	-	-	280
AU-04316	FRONT	10	30	10	35.5	51	118	80	9.5	-	-	395
AU-04318	FRONT	10	32	10	32	38	98.5	73	7 4/5	-	-	360
AU-04319	FRONT	10	32	10	32	38	91.5	66.5	7 1/2	-	-	347
AU-04320	FRONT	10	20.5	10	20.5	36	116	87	10	246	4.40	405
AU-04322	FRONT	10	21	10	24	38	114	71	9	185	3.30	395
AU-04327	FRONT	10	39.9	10	29.9	39	TBA	73.7	8.7	-	-	348
AU-04330	FRONT	10	21	10	24	38	-	66.5	9	222	3.96	368
AU-04335	FRONT	10	30	10	35.5	51	150	90	11.2	246	4.40	458
AU-04336	FRONT	10	30	10	35.5	51	149	95	11.6	258	4.60	448
AU-04338	FRONT	10	32	10	32	45.3	TBA	87.7	10.3	TBA	TBA	430
AU-04340	FRONT	10	32	10	32	TBA	TBA	TBA	TBA	TBA	TBA	466
AU-04346	FRONT	10	32	10	32	39	TBA	80	10.7	324.8	5.8	486
AU-04358	FRONT	10	21	10	24	38.2	TBA	71.6	9.3	176.96	3.16	417
AU-04363	FRONT	10	32	10	32	44	TBA	97	9.7	129.92	2.32	478
AU-04402	REAR	12	40	12	45	42	71	70	9	196	3.50	342
AU-04403	REAR	10	40	12	45	39	125	75	9 4/5	-	-	445
AU-04404	REAR	10	32	10	30	39	84	72	9 1/2	-	-	371
AU-04405	REAR	10	32	10	30	39	98	72	9 4/5	-	-	408
AU-04406	REAR	12	40	12	45	42.5	105	72	9 4/5	-	-	398
AU-04407	REAR	10	32	10	30	39	68.9	73	9.7	-	-	350
AU-04408	REAR	10	30	10	30	44	74.7	72	9.2	-	-	365
AU-04409	REAR	12	40	12	40	38	73.6	78	11 1/2	-	-	398
AU-04410	REAR	10	30	10	35.5	45	113	91	9.5	129/163	2.3 / 2.9	446
AU-04411	REAR	10	20	10	30	38	64	72	9.2	-	-	290
AU-04412	REAR	10	32	10	32	38	79	65	8.2	-	-	320
AU-04413	REAR	12	32	12	32	42	124	70	9.5	-	-	438
AU-04414	REAR	10	32	10	32	38	155	79	9	-	-	464
AU-04415	REAR	10	30	10	35.5	51	133	96	9.5	106	1.90	407
AU-04416	REAR	10	30	10	35.5	51	147	100	10.5	-	-	503

**SHOCK SPECS**

P/N	POSITION	TOP HOLE	TOP EYELET	BOTTOM HOLE	BOTTOM	TUBE	STROKE	SPRING OD	SPRING WIRE	SPRING RATE	C TO C	
		I.D. MM	WIDTH MM	I.D. MM	EYELET WIDTH MM	O.D. MM		MM	DIAMETER MM			LBS/INCH
<b>SHOCKS</b>												
AU-04417	REAR	12	40	12	45	38	131.5	74	9 2/3	-	-	448
AU-04418	REAR	10	30	10	30	38	98.5	68	8 1/2	-	-	375
AU-04420	REAR	10	20.5	16	20.5	42	118	89	10	196	3.50	390
AU-04422	REAR	15.6	21	10	24	39	130	68	7.4	81	1.45	416
AU-04427	REAR	16.2	29.9	10	29.9	29	TBA	74.1	7.6	-	-	392
AU-04429	REAR	12	40	12	32	42	TBA	82	12	-	-	395
AU-04430	REAR	10	32	14	24	38	-	66.8	9	213	3.80	346
AU-04431	REAR	10	30	10	35.5	51	139	83.1	10.4	178/243	3.18 / 4.33	417
AU-04436	REAR	10.3	30	10	35.5	51	137	90	9.7	232/236	4.14 / 4.20	408
AU-04438	REAR	12	40	12	31.85	45	TBA	94.5	12.7	TBA	TBA	450
AU-04448	REAR	10	32	10	32	38.1	TBA	62.5	6.1	TBA	TBA	266
AU-04456	REAR	10	20.5	16	20.5	41.3	107	86.8	9.3	TBA	TBA	387
AU-04459	REAR	12	40	12	40	39	TBA	80.6	11.2	TBA	TBA	342
AU-04460	REAR	12	40	12	31.85	38.8	TBA	72.9	9.6	TBA	TBA	450

**BUSHING SPECS**

NIU#	ID	OD
AU-04202B	10	23.3
AU-04206B	10	23
AU-04206C	10	23
AU-04207B	10	23
AU-04207C	10	24
AU-04209B	10	23
AU-04252B	16	20.5
AU-04253B	10	26
AU-04253C	10	25.5
AU-04254B	10	23
AU-04257B	16	22
AU-04258B	18	20
AU-04259B	10	23
AU-04312B	10	23
AU-04316C-1	10	25.5
AU-04320A	10	23.1
AU-04328B	10	23
AU-04335A	10	23.1
AU-04402B-1	12	25.5
AU-04402C-1	12	25.5
AU-04403B-1	12	25.5
AU-04403C-1	12	25.5
AU-04404B	10	23
AU-04413A	12	23
AU-04415B-1	3/8	23
AU-04415C-1	3/8	23
AU-04420A	16	28
AU-04422B	16	25
AU-04427A	16	33.2
AU-04429A	12	30.1
AU-04429B	12	23.1
AU-04430B	20	23.1

